

Project : STANDARD
 Model No : HR1140R24053MCAB

20W LED PANEL 1140x13.8mm RECTANGULAR



Input Characteristics

Mechanical Details

Input Characteristics			Mechanical Details	
1	Typical Voltage (Un)	72Vdc	Weight	100gm
2	Operating Voltage Range	70 - 75Vdc	Panel Dimensions	1140*13.8
3	Typical Current (A)	0.30 A	Length W/Mount	1140mm
4	Wattage (W) MAX	22W	Width	13.8mm
5	Nos Of LED	120	Center to Center (CTC)	175x85mm
6	LEDs Aray Combination	24in Series 5 in parallal	Thickness	1.6mm
7	Viewing Angle	120°Degree		
8	LED Color Tempreture	6500K	PCB Material	MCPCB
9	Luminous flux	2640 lm*	Polarity Connection	On PCB
10	Operating Tempreture	-15° to 50°C	Input Connections	Wires
11	Maintenace of Lumen output -L70	50,000 hours at 25°C	Wires Colors and Polarity	
12	LED Make	BRIDGELUX	Positive (+ve)	RED
13	LED Package	2835	(Negative (-ve)	BLACK

Environmental Operating Details

Features

Environmental Operating Details			Features	
1	Minimum Ambient Temperature	-30°C	1. High System Efficiency - 110lm/W. 2. High Color Redering and good light uniformity. 3. Energy Saving. 4. Improve working enviroment. 5. Long life time: 25,000 hours minimum. 6.* Lumen Flux depend on Reflector/Diffuser.	
2	Maximum Ambient Temperature	50°C		

Ordering Information

Sr No	Model Number	Description	Case Lot
1	HR1140R24053MCAB	LED PANEL 1140X13.8mm Rectangular	50

Add:-SR.NO. 14, Dhadge ind Estate, plot no.3 Singhgad Road, Nanded Phata, Pune-411041, Maharashtra(India),mobile no:8668334832
 Email : marketing@hrindustry.net ,hrindustry12@outlook.com , web:- www.hrindustry.net , Contact:- 9049378851,968999702